

Data sheet

WDS® Granulate

ENGLISH

Metric information - Page 2
Imperial information - Page 3

Description

WDS® Granulate is a microporous insulation material which has an extremely low thermal conductivity coefficient giving it very good insulating properties.

WDS® Granulate consists of inorganic silicates. The main constituent is fumed silica; the other components are infrared opacifiers.

WDS® Granulate is non-flammable and meets the requirements of DIN EN 13501-1; part 1, A1.

Application

WDS® Granulate is a free-flowing WDS® grade that offers excellent insulating properties. It is specially developed for filling insulation panels. The inorganic granules are specially modified for the filling of voids and spaces of complex geometry.

WDS® Granulate is also successfully used as insulation material in the following areas:

- Industrial chimneys
- Measuring instruments
- Industrial plants
- Insulated vessels
- Special machinery

Advantages of WDS® Granulate:

- Controls energy emissions, precisely
- Reduces weight and volume
- Increases heat retention
- Increases effective volume

Processing

WDS® Granulate is generally filled under suction or vibration. In larger rooms in which the previous methods cannot be applied, the assistance of external vibrator facilities are available. In all cases there is a compression of the granules. To ensure there is no settling during use, the granules are mechanically compressed by up to 10%. The individual granules consist of a greater volume, i.e. they expand, when destroyed.

Form of delivery

WDS® pellets are supplied in a granular form delivered in bulk bags.

Restrictions of use

WDS® Granulate has a non-porous surface therefore it is sensitive to all liquids that can wet it; this includes substances such as water, oil, petroleum spirit, since they can destroy the nanopores.

Water vapor does not have a destructive effect on WDS® Granulate.

Shelf life

- WDS® Granulate, has unlimited shelf life if it stored properly
- WDS® Granulate must be handled and stored in dry conditions.
- WDS® Granulate is resistant to diffusion by atmospheric humidity (water vapor).

Composition

Silicon dioxide	SiO ₂	approx. 70%
Silicon carbide	SiC	approx. 30%

Thermal Shock Resistance

WDS® Granulate is insensitive to high and low temperature thermal shocks.

Safety directions

WDS® Granulate is not a hazardous substance according to the EU Directive 2006/1907/EEC. WDS® Granulate does not use any dangerous decomposition substances and according to current knowledge, it does not cause any problems to human health or the environment.



Data sheet

WDS® Granulate

Metric information

Physical properties	
Colour	Grey
Nominal density kg/m ³	110 - 135
Classification temperature °C	1000
Recommended temperature of use °C	950
Tapped density kg/m ³	130 - 160
Vibration density kg/m ³	180 - 220
Thermal conductivity at average temperature of 22.5°C and density 165kg/m ³ W/m·K	0.025
with density 200kg/m ³ W/m·K	
	@50°C 0.026
	@200°C 0.027
	@400°C 0.035
	@600°C 0.049
	@800°C 0.068

The above data are only intended as a guide and should not be used in preparing specifications.

Contact

Europe:

Telephone:
+44 (0) 151 334 4030

E-mail:
marketing.tc@morganplc.com

North America:

Telephone:
+1 (706) 796 4200

E-mail:
northamerica.tc@morganplc.com

South America:

Telephone:
+54 (11) 4373 4439

E-mail:
marketing.tc@morganplc.com

Asia:

Telephone:
+65 6595 0000

E-mail:
asia.mc@morganplc.com

Porextherm:

Porextherm
Dämmstoffe GmbH
Heisinger Straße 8/10
D-87437 Kempten

Telephone:
+ 49 (0)831 - 575360
Fax:
+ 49 (0)831 - 575363

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

Whilst the values and application information in this datasheet are typical, they are given for guidance only. The values and the information given are subject to normal manufacturing variation and may be subject to change without notice. Morgan Advanced Materials - Thermal Ceramics makes no guarantees and gives no warranties about the suitability of a product and you should seek advice to confirm the product's suitability for use with Morgan Advanced Materials - Thermal Ceramics.

Morgan Advanced Materials plc Registered in England & Wales at Quadrant, 55-57 High Street, Windsor, Berkshire SL4 1LP UK Company No. 286773

Data sheet

WDS® Granulate

Imperial information

Physical properties	
Colour	Grey
Nominal density pcf	7 - 8.6
Classification temperature °F	1832
Recommended temperature of use °F	1742
Tapped Density pcf	8.1 - 10.0
Vibration Density pcf	11.2 - 13.7
Thermal Conductivity 72.5°F with density 10.3 pcf, BTU·in/sq.ft·h·°F	0.17
with density 12.49 pcf BTU·in/sq.ft·h·°F	
	@122°F 0.18
	@392°F 0.19
	@752°F 0.24
	@1112°F 0.34
	@1472°F 0.47

The above data are only intended as a guide and should not be used in preparing specifications.

Contact

Europe:

Telephone:
+44 (0) 151 334 4030

E-mail:
marketing.tc@morganplc.com

North America:

Telephone:
+1 (706) 796 4200

E-mail:
northamerica.tc@morganplc.com

South America:

Telephone:
+54 (11) 4373 4439

E-mail:
marketing.tc@morganplc.com

Asia:

Telephone:
+65 6595 0000

E-mail:
asia.mc@morganplc.com

Porextherm:

Porextherm
Dämmstoffe GmbH
Heisinger Straße 8/10
D-87437 Kempten

Telephone:
+ 49 (0)831 - 575360
Fax:
+ 49 (0)831 - 575363

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

Whilst the values and application information in this datasheet are typical, they are given for guidance only. The values and the information given are subject to normal manufacturing variation and may be subject to change without notice. Morgan Advanced Materials - Thermal Ceramics makes no guarantees and gives no warranties about the suitability of a product and you should seek advice to confirm the product's suitability for use with Morgan Advanced Materials - Thermal Ceramics.

Morgan Advanced Materials plc Registered in England & Wales at Quadrant, 55-57 High Street, Windsor, Berkshire SL4 1LP UK Company No. 286773